

MS-320

COMPOSITION

Packing manufactured by MONTERO from continuous aramid filament, which are impregnated with PTFE and other lubricants.

Packing MS-320 is an reliable option and economic for sealing equipment, it could be manufactured with graphite finished. **Ref. MS 320 G**

Perfectly adjustable to every kind of groove in centrifugal and alternative pumps and every rotary equipment.

Packing used in whole services but in special for sugar and paper factories and for high abrasive and viscous fluids where mechanical resistance of the continuous aramid prevent from detrition.

Follow carefully MONTERO's installation procedures.

PARAMETER

MS-320	Maximum working conditions
TEMPERATURE (°C)	250
PRESSURE (Bar)	100
VELOCITY (m/s)	15
P-H	2-12

APLICACIONES

Pressure and dynamic equipment, turbines, compressors and, on the whole, every centrifugal movement at high pressures.

Pumps & equipment in:

POWER & NUCLEAR PLANT
PAPER & PULP MILL.
CHEMICAL & PETROCHEMICAL INDUSTRY.
SUGAR & FOOD INDUSTRY.
CEMENT PLANT.
STEEL & FOUNDRY FACTORIES.
MARINE INDUSTRY, etc.



Montero®

FIBRAS Y ELASTOMEROS, S.A.

El Juncal, s/n. Edificio Fuentes 2º Local 11
48510 Valle de Trapaga, Vizcaya, España.
Tel. + 34-94 418 00 11 Fax. + 34-94 418 91 83
e-mail: access@monterofye.com
http://www.monterofye.com

The data given on this technical sheet should not be used as applications limits, but as guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

